

The New Standard of Level

Glass-Trac Level-Trac Steam-Trac Magne-Trac 210-00 04/27/2023

13960 South Wayside • Houston, TX 77048 Tel: +1 (281) 240-0440 • Fax: +1 (281) 240-2440

STEAM-TRAC MODEL SERIES SUMMARY

<u> \$T-350</u>

RATING: 350 PSI WSP

- FOR 250/300 + PSI OPERATING, USE ST-450 W/ MICA
- SECTIONS DO NOT OVERLAP, NOT REQUIRED
- IF WATER PH IS OVER 9, ST-450 IS RECOMMENDED
- FORGED CARBON STEEL COVERS
- CADMIUM PLATED B7 BOLTING
- SPRING WASHERS

ST-450

RATING: 450 PSI WSP

- SECTIONS OVERLAP
- FORGED CARBON STEEL COVERS
- CADMIUM PLATED B7 BOLTING
- SPRING WASHERS
- HIGH QUALITY MICA SHIELDS
- ILLUMINATOR STRONGLY RECOMMENDED (WHEN USING MICA)

ST-1000

RATING: 1,000 PSI WSP

- SECTIONS OVERLAP
- HEAVY DUTY CHAMBER
- FORGED CARBON STEEL COVERS
- CADMIUM PLATED B7 BOLTING
- SPRING WASHERS
- HIGH QUALITY MICA SHIELDS
- ILLUMINATOR STRONGLY RECOMMENDED (WHEN USING MICA)

ST-1600

RATING: 1,600 PSI WSP

- SECTIONS OVERLAP
- HEAVY DUTY CHAMBER AND COVER
- FORGED CARBON STEEL COVERS
- HEAVY DUTY CADMIUM PLATED B7 BOLTING
- SPRING WASHERS
- HIGH QUALITY MICA SHIELDS
- ILLUMINATOR STRONGLY RECOMMENDED (WHEN USING MICA)

\$TB-3000

RATING: 3,000 PSI WSP

- FOR ALL PRESSURE RANGES TO 3,000 PSI
- SECTIONS DO NOT OVERLAP
- CADMIUM PLATED B7 BOLTING
- RUBY MICA SHIELDS
- HIGH QUALITY GASKETING
- PORTED TYPE, MUST USE ILLUMINATOR
- PACKAGED WITH BI-COLOR L.E.D. ILLUMINATOR
- ILLUMINATOR REQUIRED PER ASME SECTION 1 CODE